

TECHNICAL DATA SHEET: **TRANSVIR 60 LK**

Kraft 100% white cellulose, not treated, with a compact and glazed surface, that lets it proper to receive sublimatic inks, without they enter into the fibers, guaranteeing a good release during the transfer
For digital transfer printing with water-based sublimating ink.

TECHNICAL SPECIFICATIONS

- WEIGHT	60 gsm/sqm
- THICKNESS	80 my
- ROLLS LENGTH	270 mt
- AVAILABLE WIDTHS	162 cms
- INNER ROLL DIAMETRE	3"
- UTILISATION	transfer on all polyester fabrics, above all clothing and interiors ones Very good for middle/high ink charges Transfer with calender
- APPLICATION TEMPERATURE	it changes according to the fabric and we suggest to test the paper before using it. Generally, the application temperature is 195-205°C for 45-60 seconds
- QUALITY	very good drying time very good definition of printing details good colour releasing no ghost effect after transfer very good dimensional stability

STORAGE

- Keep dry
- It's suggested the utilisation in environment with a moisture of 45% and 23°C
- It's suggested to leave the paper without packing before using it
- Duration: 2 years if stocked in proper conditions and in the original packing

PARTICULAR EQUIPMENTS AVAILABLE ON REQUEST

VIRAX BORGHİ ITALIA S.R.L.

Sede: Via Edison, 2 20090 Segrate (MI) - Tel. 02 26922041 - virax@virax.it

Filiale Veneto: Via dell'Artigianato, 13 31033 Castelfranco Veneto (TV) - Tel. 0423 720155

Filiale Centro Italia: Z.na Industriale Vallecupa 64010 Colonnella (TE) - Tel. 0861 749563

Filiale Toscana: Via Provinciale di Mercatale, 140 50059 Vinci (FI) - Tel. 335 6570468